

Gestetner

TOTAL DOCUMENT SOLUTIONS



MP 161F/MP 161SPF



Aficio™

THE OFFICE DOCUMENT DEVICE
WITH A BRIGHTER APPROACH

SPECIFICATIONS

MP 161_F/MP 161_{SPF}

Printer (MP 161_{SPF})

Print speed

16 prints per minute

Printer language

Standard: PCL5e, PCL6, RPCS
Option: Adobe PostScript 3

Resolution

600 x 600dpi

Interface

Standard: USB 2.0
Ethernet 10 base-T/100 base-TX
Option: Wireless LAN (IEEE802.11b)
Bi-directional IEEE1284
Bluetooth

Network protocol

TCP/IP, IPX/SPX, SMB, AppleTalk

Supported environments

Windows 98/Me/NT4.0/2000/XP/
Server 2003

Copier

Copying process

Twin laser beam scanning and electro-
photographic printing

Copy speed

16 copies per minute

Resolution

600dpi

Multiple copy

Up to 99

Warm up time

Less than 30 seconds

First output speed

Less than 7.5 seconds

Zoom

50 - 200% (in 1% steps)

Memory

MP161F: 128MB (Shared)
MP161SPF: 384MB (Shared)

Paper input capacity

Standard: 1 x 250-sheet paper tray
1 x 100-sheet multi-bypass
tray
Maximum: 850 sheets

Paper output capacity

Standard: 250 sheets (internal tray)

Paper size

Standard tray: A5 - A4
Bypass tray: A6 - A4
Duplex: A4

Paper weight

Standard tray: 60 - 90g/m²
Bypass tray: 60 - 157g/m²
Duplex: 64 - 90g/m²

Dimensions (W x D x H)

485 x 450 x 481mm

Weight

Less than 29kg

Power source

220 - 240V, 50/60Hz

Power consumption

Operation: Less than 900W
Energy saver mode: Less than 30W

Scanner (MP 161_{SPF})

Scan speed

Maximum 22 originals per minute

Resolution

Maximum 100 - 600dpi

Original size

A5 - A4

Bundled drivers

Network, TWAIN

Scan to e-mail

SMTP, TCP/IP or POP3 before SMTP

Destination addresses

Maximum 100 per job

Stored destination addresses

Maximum 150

Address book

Via operation panel, LDAP, Web Image
Monitor or SmartDeviceMonitor

Scan to folder

SMB, NCP or FTP protocol

Destination

Maximum 32 folders per job

Fax

Circuit

PSTN, PBX

Compatibility

ITU-T G3

Modem speed

Maximum 33.6kbps

Compression method

MH, MR, MMR, JBIG

Scanning speed

2 seconds

Speed dial

Maximum 150 numbers

One touch dial

Maximum 16 numbers

Memory capacity

4MB (320 pages)

Software Solutions (MP 161_{SPF})

SmartDeviceMonitor
Web SmartDeviceMonitor 2
Web Image monitor
DeskTopBinder Lite

Options

- 1 x 500-sheet paper tray
- Counter Interface
- Cabinets (small, large)

Company management systems applied during the manufacturing of all Gestetner products conform to ISO9001 quality and ISO14001 environmental management standards.

In compliance with EU RoHS directive (RoHS: Restriction of Hazardous Substances).

We reserve the right to make amendments to the technical specifications and external appearance of this equipment. Please note that the full range of machines and options shown in this publication may not always be available. All brand and product names are recognised, and hereby acknowledged, as registered trademarks of their respective owners.



Adobe PostScript 3



GMP161SPF4GBD

Gestetner

Part of the NRG group

www.gestetner.com

